
VISION

LED Signage Lights



An exit signs is a device in a public facility denoting the location of the closest emergency exit. Exit signs are a perfect application for the use of Light Emitting Diodes(LED's), which are excellent for exit sign illumination.

Led exit signs provide numerous benefits over their more wasteful counterparts in the form of energy savings, financial savings, lifespan of light and ease of replacement.



300 MM

| TECHNICAL SPECIFICATIONS | | | | | |
|------------------------------|---------------------|--|--|--|--|
| On/Off Cycles: | 35000 | | | | |
| Correlated Color Temperature | 5800K | | | | |
| Color Rendering Index | >80 | | | | |
| PF | >0. 9 | | | | |
| THD | <25% | | | | |
| Finishing Color | Matt White / Silver | | | | |
| Driver Integrated (Yes/No) | Yes | | | | |

ELECTRICAL SUPPLY

Frequency (Hz) Mains voltage (VAC) 50-60 Hz 220-240 VAC

APPLICATION CONDITIONS

Operating Temperature range -20 to +50 °C

Nominal Temperature 25 °C

| MATERIAL PROPERTIES | | | | | |
|---|---|--|--|--|--|
| Optical Material | Polycarbonate diffuser | | | | |
| Housing | All noncorrosive hardware (Aluminium) | | | | |
| Features | | | | | |
| > Directs towards the exit in disastrous | | | | | |
| situations | | | | | |
| <pre>LED light source f reduced maintenance</pre> | or longer life and | | | | |

> LED provides longer life and lower power consumption.

➢ Easy to install.

≻Double sided display.

| PART NO | POWER (Watt) | Backup (Hr) | Size | Battery Size | MRP |
|------------|--------------|-------------|------|--------------------|------|
| VISION-Z-5 | 5 | NA | 2800 | NA | 2800 |
| VISION-S-5 | 5 | 2Hr | 3400 | Samsung 3.7 V 2600 | 3400 |



Text, graphics and color you can customize as per the requirement