

HLX LED units are the brightest in their class. With their rugged construction they are ideal for machine tools, and food and beverage processing equipment. Available in wide or slim package HLX LED units are the brightest in their class. With their rugged construction they are ideal for machine tools, and food and beverage processing equipment. Available in wide or slim packages, with either Standard or High Luminance (brighter, wider range) options. The design of these LED lights provides equally brilliant light at the centre or edges of the units.

So, with either Standard or High Luminance (brighter, wider range) options. The design of these LED lights provides equally brilliant light at the center or edges of the units.

HLX LED hand lamps can be used in the areas:

- Electricity providers
- Mills
- Biogas plants
- Gas stations
- Tank automotive
- Aerospace industry
- Aircraft maintenance & inspection
- Oil rigs
- Offshore, shipyards etc.

Features :

- LED hand lamp with 1W POWER-LEDs for high light output, 6500 Kelvin
- Protection category IP65
- Operating range 230 volt, 110 volt, 42 volt, 24 volt, 12 volt available
- 3m cable (Oil resistant cable H07RN-F or higher cable length can be provided on request)
- Holding tube made out of MS with rubber grip
- End-parts made out of ABS material



Part Number	HLX-7W	HLX-15	HLX-20	HLX-30
Lamp Type	7W	15W	20W	30W
Input Voltage (AC/DC)	24V	24V	24V	24V
LED Luminous Flux	700 lm	1500 lm	2000 lm	3000 lm
LED Luminous Efficacy	100 lm/W	100 lm/W	100 lm/W	100 lm/W
Color Temperature	Cool White	Cool White	Cool White	Cool White
LED Viewing Angle	360°	360°	360°	360°
Working Lifetime:	50,000 Hour	50,000 Hour	50,000 Hour	50,000 Hour
IP Rating:	IP67	IP67	IP67	IP67
Working Temperature	-20° - 55°C	-20° - 55°C	-20° - 55°C	-20° - 55°C
Housing	PC and Al	PC and Al	PC and Al	PC and Al
Weight	0.7Kg	0.7Kg	0.7Kg	0.7Kg
Cable Length	3 M	5 M	8 M	8 M
Warranty	2 years	2 years	2 years	2 years